

Storm (POU Water Cooler)



Crystal Mountain now introduces the Storm point of use water dispenser, following the successful introduction of its counterpart, the Storm Bottom-Load water dispenser.

The Storm point of use water dispenser features an easy to remove reservoir system that takes less than a minute to change. The LED indicator tells you when it needs to be replaced. Servicing has never been easier. With its contemporary design, attractive finish, concealed faucets and easy maintenance, the Storm is sure to dazzle in any environment.

Model: Storm: *Hot & Cold*



LED Night Light
replace **SmartFlo SF-1**
Indicator



Unique Sliding front Door



Replaceable Reservoir System -
SmartFlo SF-1 Water Cartridge

Specifications:

ITEM		SPECIFICATIONS
Power rating		Single phase 100-115VAC 60Hz
Standard current		Hot & Cold: 4.8~5.3A
Power Consumption	Cold	70W
	Hot	500W
Cold	Compressor	Single phase motor
	Refrigerant	R134a
	Temp range	39.2-50°F (4-10°C)
	Temp control	thermostat (ON 8 °C ±1.5°C, OFF 4 °C ±1.5°C)
	Volume of Cold Reservoir	0.4 us gal (1.6L)
Hot	Heater	Internal heater
	Temp range	168.8-197.6°F (76-92°C)
	Safety device	Bimetal (Manual reset: 95 °C OFF)
	Temp control	Bimetal (185°F) (85°C)
	Capacity (Internal Heater)	0.3 us gal (1.1L)
Refrigerant charge		1.2 oz (35g)
Noise(sound power level)		Pump:55dB(A); Compressor:43dB(A)
Product weight		Hot & Cold: 32.0 lb (14.5kg)



Product boxed weight	Hot & Cold: 35.7 lb (16.2kg)
POU assembly weight	4.5 lb (2.0kg)
POU assembly boxed weight	5.7 lb (2.6kg)
Product dimensions	12.6"(W) X 13.4"(D) X 43.9"(H)
	320(W) x 340(D) x 1116(H)mm
Product boxed dimensions	13.4" (W) X 15.0" (D) X 45.9" (H)
	340(W) X 380(D) X 1165(H)mm
Loading quantity	20' Container: 204 Units
	40' Container: 420 Units
IEC protection class	Class 1
Certifications	C-UL-US, CE, CB

This Company has a policy of continuous development and reserves the right to change specifications without notification. For further clarifications, please contact us at sales@crystalcoolers.com